

R9824FE 726cc, KAWASAKI FS691V Engine

4WD

Cutting Width **980mm**

Sliding Seat

Engine Cover Fully opens

Fan for Dust Exhaust

Hourly Meter

LED Head Light

Max. Slope

25°



《 Amazing 4WD 》

Auto-shift 4WD & Speedy Turning. That can reduce fuel consumption. Swift from 2WD to 4WD automatically, when necessary.



Wide Vertical Axle Adjustment
Power Traveling

《 Powerful Slope Climbing 》

A KAWASAKI High Power Engine provides great performance on slopes and bumpy grounds!!



Min. turning radius
2,200mm

《 Useful Seat Sliding Function 》

By using the seat sliding function, you can cut grass next to the tree trunk.



Slide the seat on your right

ECO-Drive Mode

An Eco-Light turns on when driving at the most fuel-efficient speed. Chose the driving mode depending on conditions.

Low center of gravity

The low design Atex Ride-on Brush Cutter can travel in narrow, low and bushy spaces.



Designed for Easy Maintenance

■ The Engine Cover Fully Opens

The engine cover opens fully, inspecting or changing and refilling the engine oil can be done easily.



Fully OPEN!!

■ Easily wash blades and inside the cutting-blade cover

Connect a hose to the cutting-blade washing pipe. Start the engine and turn the cutting-blade clutch "ON" and then supply water. Just 3 minutes rotating can wash inside the cutting-blade cover.



Connect a water hose to the washing pipe



Rotate the cutting blade for 3 minutes

Specifications		R9824FE	
Dimensions (LxWxH/mm)		1,965 x 1,090 x 875	
Weight (Kg)		340	
Wheel Base (mm)		1,320	
Tread (mm)		FF 830, RF 785	
Mowing	Cutting Width (mm)	980	
	Cutting Height (mm)	10 ~ 100 (stepless)	
	Knife Shape	Free Knife x 2	
	Max. working efficiency (a/h)	98	
Traveling	Speed	Forward (km/h)	0 ~ 10.0
		Reverse (km/h)	0 ~ 8.5
	Wheel	Front	4.00-7-4PR (φ 400)
		Rear	17x8.00-8-4PR (φ 440)
	Handling Type	Handle with Knob	
	Min. Turning Radius (mm)	2,200	
Max. Inclination (°)	25		
Operation		HST Pedal / HST Lever	
Model		Kawasaki FS691V	
Type		Air-cooled, 4-cycle 2-cylinder OHV gasoline engine	
Displacement (L (cc))		0.726 (726)	
Output/rpm (kw(ps)/rpm)		Net 12.9 (17.5) / 3,000 (Max 15.3 (20.8) / 3,600)	
Fuel		Unleaded Automotive Gasoline	
Fuel Tank Capacity (Liter)		14	
Starter		Electric Starter	
Seat	Adjustment (mm)	Forward - Reverse 60	
	Slide (mm)	0 · 180 · 240 · 300 (3 Steps)	
Head Light		LED	